

OP-5S5108A,OP-5S5108B,OP-5S5115B,OP-5S5115C



OP-5S5108A
OP-5S5108B **F**
OP-5S5115B
OP-5S5115C
 Air shut off
 Handle exhaust
 自動斷氣
 下排氣

Specifications:

OP-5S5108 / OP-5S5115: Push start, Air shut off, Rear exhaust

- With push-start device, all parts stop working automatically while reaching the torque.
- Rear exhaust, low noise, low air consumption, and save energy.

Application:

- Apply to release or fasten heavy-precise screws.
- Apply especially to industry assembly lines such as computer, instrument, and electric.

MODEL	Screw Size	MAX.	Free	Air		Overall		Air	Net		Sound
	Capacity	Torque	Speed	Consumption		Length	Inlet	Weight		Level	
	mm	Nm	rpm	l/min	cfm	mm	inch	P.T	kg	lb	dB(A)
OP-5S5108A	5	2.8~4.0	800	198	7	195	7.68	4-Jan	0.98	2.09	80
OP-5S5108B	4	1.9~2.8	800	198	7	195	7.68	4-Jan	0.98	2.09	80
OP-5S5115B	4	1.4~2.6	1400	198	7	195	7.68	4-Jan	0.98	2.09	80
OP-5S5115C	3.5	0.9~1.6	1400	198	7	195	7.68	4-Jan	0.98	2.09	80