

JKK Ceramic Fiber Stone



☆ In order to reach the best performance, we recommend that the stone should be held up-right, making an angle of approx. 30°~45° to the work-piece.

FEATURES & SPECIFICATIONS

Grit size	#180	#250	#280	#360	#400	#500	#700	#1200
Color	Brown	Orange	Black	Navy Blue	Blue	Green	Yellow	Red
Code	C	O	D	N	B	G	Y	R

規格 / Specifications:



T x W (ØD)	Grit size & Order No.						
(ØD x L)	#180	#250	#280	#360	#400	#700	#1200
1 x 4 x 100	JKC-1004	JKO-1004	JKD-1004	JKN-1004	JKB-1004	JKY-1004	JKR-1004
1 x 6 x 100	JKC-1006	JKO-1006	JKD-1006	JKN-1006	JKB-1006	JKY-1006	JKR-1006
1 x 10 x 100	JKC-1010	JKO-1010	JKD-1010	JKN-1010	JKB-1010	JKY-1010	JKR-1010
Ø3 x 100	JKC-03	JKO-03	JKD-03	JKN-03	JKB-03	JKY-03	JKR-03

Recommendation :

Grit size	Application
#180、#250、#280	To remove the rough machining surface or hard EDM scale of tool and die steels.
#36、#400	General lapping of finer surface scratch line of tool & die steels.
#700、#1200	Fine polishing & finishing.
Ø3.0mm round	It can be used liked grinding point(maxx. length 50mm),or by sharpening it for detail lapping.

In order to reach the best performance, we recommend that the stone should be held up-right, making an angle of approx. 30°~45° to the work-pie